

Foamtech® “N”

Sponge Rubber Joint Material

Description:

Foamtech® “N” is a Closed Cell Neoprene Sponge expansion joint filler. It is the ultimate solution for masonry expansion joints for brick and block. **Foamtech® “N”** meets and exceeds all ASTM D 1056 specifications for Closed Cell Sponge Neoprene expansion joints in residential, commercial, and industrial applications. Neoprene Sponge Rubber is available in multiple densities/types to meet a wide range of specifications


Use:

Foamtech® “N” helps prevent clogging of expansion joint with mortar and is the accepted material for brick and block expansion joint fillers. It can be used in almost any residential, commercial or industrial application.

Foamtech® “N” can be custom cut for your jobsite needs and is available with or without PSA (Pressure Sensitive Adhesive).

Features:

- **Foamtech® “N”** – A high quality, closed cell Neoprene Sponge Rubber
- **Flexibility** – Will not break or crack when used in masonry joints
- **Accepted** – Currently used by both residential and commercial contractors
- **PSA** – Available with or without Pressure Sensitive Adhesive
- **Economical** – Easily cut and handled on any jobsite, and available in 50' rolls or flat strips



Foamtech® “N”	
Color	Black
Density, Apr. (lbs/ft ³)	4.5 PCF
Polymer	Neoprene /SBR
Temp. Resistance, Low ° F High ° F Continuous	-40 ° F + 150 ° F
Compression Deflection 25% PSI Compression Varies with thickness	2 – 5 PSI
Shore 00 Durometer (Apr. Ave.)	45
Water Absorption by weight Max ASTM Method D 1056	5% (10% Allowed)
Flame Resistance FMVSS302	Pass



6553 West 400 North • Greenfield IN • 46140

Ph: (317)891-1010 • Fx: (317)891-1019 • Toll Free: (800)253-4237

On the web: www.nmwinc.com